

We claim:

1. A method of forward enhanced CMEA encryption or decryption cryptoprocessing for each message in a call, for use in a CMEA encryption system employed in a wireless telephone system comprising the steps of:

introducing an unprocessed message or encrypted message;

creating one or more secret offsets;

performing a first transformation on the unprocessed message to produce a first transformed message;

performing an iteration of the CMEA process on the first transformed message to produce an intermediate ciphertext message, the iteration of the CMEA process employing an enhanced tbox function using an involutory lookup, the inputs to the enhanced tbox function being subjected to a permutation using one or more of the secret offsets to produce a permutation result; and

performing a second transformation on the intermediate ciphertext message to produce a final processed message,

2. The method of claim 1 wherein the one or more secret offsets include a first and a second secret offset.

3. The method of claim 2 wherein the step of generating each of the first and second offsets includes combining ones of a plurality of secret values with a an external value.

4. The method of claim 3 wherein the secret values include two 8-bit values for each offset.

5. The method of claim 4 wherein the external value is an 8-bit value.

6. The method of claim 5 wherein the first offset for an nth message of a call is expressed by the equation $\text{offset1} = ((K_0 + 1) * CS_n \bmod 257) \oplus K_1 \bmod 256$, where K_0 and K_1 are ones of the secret values and CS_n is an external value for the nth message, and wherein the

09120763-072296

subjected to a permutation using one or more of the secret offsets to produce a permutation result;
and

performing a second inverse transformation on the intermediate ciphertext message to
produce a final processed message.

10. The method of claim 9 wherein the one or more secret offsets include a first and a
second secret offset.

11. The method of claim 2 wherein the step of generating each of the first and second
offsets includes combining ones of a plurality of secret values with an external value.

12. The method of claim 11 wherein the secret values include two 8-bit values for each
offset.

13. The method of claim 12 wherein the external value is an 8-bit value.

14. The method of claim 5 wherein the first offset for an nth message of a call is
expressed by the equation $\text{offset1} = ((K_0 + 1) * CS_n \bmod 257) \oplus K_1 \bmod 256$, where K_0 and K_1
are ones of the secret values and CS_n is an 8-bit external value for the nth message, and wherein the
second offset for an nth message of a call is expressed by the equation $\text{offset2} = ((K_2 + 1) * CS \bmod$
 $257) \oplus K_3 \bmod 256$, where K_2 and K_3 are ones of the secret values and CS_n is an 8-bit external
value for the nth message.

15. The method of claim 14 wherein the first inverse transformation includes the steps of
performing random byte permutation, involutory lookup with feedback, and bit trading on each octet
of the unprocessed message, wherein the steps of bit trading and random byte permutation each
employ the second secret offset, and wherein the step of involutory lookup with feedback employs
both the first and second secret offsets.

16. The method of claim 15 wherein the second inverse transformation includes the steps
of performing random byte permutation, involutory lookup with feedback, and bit trading on each

09120763-072298